

ALL IN ONE Solar street light



- Solar powered outdoor lighting
- Easy installation. No cable needed
- ➢ Lithum-ion LiFePO4
- High efficiency Mono solar panel
- Famous brand LED chip from **EPISTAR and Bridgelux**
- Mounted convenient, pole, wall, tree etc
- Modularity design. Easy assemble and maintenance
- Compact volume and light weight design saves freight cost and installation cost
- > Rust-proof, dustproof and **IP65 waterproof** Safety and reliability

odel		NSP50 (no sensor)	NSP60 (no sensor)
	Max power	12V 50W	12V 60W
	Led chip	Bridgelux , USA	
	Lumen (LM)	6000Lm	7200Lm
LED Light	Life time	50,000hours	
	Max power	18V/80W	18V/90W
	Solar cell	High efficiency, Mono	
Solar panel	Life time	25years	
	Capacity	39AH	42AH
	Туре	Lithum-ion LiFePO4	
Battery	Life time	5 years	
Charging	By sun	6-10 hours effective sunlight	
Lighting	discharge	>12hours	>12hours
Work temp	Range(℃)	Charging:0°C~+60°C, discharging: -20°C~+60°C storage:0°C~+45°C	
Colour temp	Range(k)	6000-6500k	
Height	Range (m)	8-9m	8-9m
Spacing	Range (m)	25-30m	25-30m
Work mode	Customized available	Time control, Full power +dimming	Time control, Full power +dimmin
Material	Aluminium alloy		
Certificate	CE / ROHS / IP65		
Warranty	3years		
	Product size(mm)	1080*450*153	1080*450*153
	Product weight	24kg	26 kg
	Carton size(mm)	1190*520*220	1190*520*220
Packing & Weight	GW .for carton	24.5kg	26.5kg
	20GP	231sets	231sets
Packs Containers	40HQ	516sets	516sets