




FT-ENERGY FLOATING PV SYSTEM

Floating PV




Product Feature

- Easy to install and maintenance.
- Increase durability by using sunscreen: UV class 8 (PA +++)
- Use a buoy (floating) suitable for Migration testing in Drinking water standard.
- Intellectual property rights including patent and design.
- Thickness of PV : 4 mm or more.


Floating Structure Specification

Part name	Size	Weigth	Material	Buoyancy
Main block	2,300*1760*438	25kg	MDPE	320kg
Passage block	2,300*650*220	15kg	MDPE	175kg
Tray block	800*1760*220	15kg	MDPE	180kg
load block A	800*1760*220	12kg	MDPE	175kg
load block B	2,300*1760*220	30kg	MDPE	450kg
load block C	2,300*1760*220	30kg	MDPE	450kg
load block D	650*800*220	12kg	MDPE	57kg
Connect pin	220*50	0.2kg	MDPE	-
Bracket A	80*50*5	0.1kg	SUS	-
Bracket B	120*50*50	0.1kg	SUS	-

Main Block Structure



5 Step Assembly and installation



FT-ENERGY CO., Ltd.

70/12 Moo.6, Ladsawai, Lumlukka, Pathumthani 12150 Thailand Tel: +662 159 0830, Fax: +662 159 0831, Website: www.ft-energy.co.th